

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G01N 21/27		A1	(11) International Publication Number: WO 97/19340
			(43) International Publication Date: 29 May 1997 (29.05.97)
(21) International Application Number: PCT/CA96/00758			(81) Designated States: JP, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(22) International Filing Date: 21 November 1996 (21.11.96)			
(30) Priority Data: 60/007,407 21 November 1995 (21.11.95) US			
(71) Applicant (for all designated States except US): CME TELEMETRIX INC. [CA/CA]; 560 Parkside Drive, Waterloo, Ontario N2L 5Z4 (CA).			
(72) Inventors; and (75) Inventors/Applicants (for US only): CADELL, Theodore, E. [CA/CA]; 290 Sandowne Drive, Waterloo, Ontario N2K 2C2 (CA). SAMSOONDAR, James [CA/CA]; 5556 Whistler Crescent, Mississauga, Ontario L4Z 3R5 (CA).			
(74) Agent: RUDOLPH, John; Gowling, Strathy & Henderson, Suite 1020, 50 Queen Street North, Kitchener, Ontario N2H 6M2 (CA).			

(54) Title: APPARATUS AND METHOD FOR RAPID SPECTROPHOTOMETRIC PRE-TEST SCREEN OF SPECIMEN FOR A BLOOD ANALYZER



(57) Abstract

A method and apparatus for use in respect of samples which are assessed for quality prior to testing in a clinical analyzer. The method and apparatus identify parameters such as gel level and height of fluid above the gel in blood samples, where appropriate, for the purposes of positioning the specimen for determination of interferents. Such interferents include hemoglobin (Hb), total bilirubin and lipids. These interferents are determined by measurement of absorption of different wavelengths of light in serum or plasma, or other specimens, which are then compared with values obtained through calibration using reference measurements for the respective interferents in serum or plasma or other type of specimen. Determinations of temperature of the specimen, as well as specimen type, for example whether the specimen is urine or plasma or serum, may also be carried out.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

- 1 -

**APPARATUS AND METHOD
FOR RAPID SPECTROPHOTOMETRIC PRE-TEST SCREEN
OF SPECIMEN FOR A BLOOD ANALYZER**

5 TECHNICAL FIELD

This invention relates to spectrophotometry and the spectrophotometric analysis of blood samples. In particular, this invention relates to a method and apparatus for providing a rapid pre-test determination of interferent concentration, specimen type and physical properties of a blood sample for a blood analyzer by
10 measurement of absorbance or reflectance.

BACKGROUND ART

15 Clinical laboratory tests are routinely performed on the serum or plasma of whole blood. In a routine assay, red blood cells are separated from plasma by centrifugation, or red blood cells and various plasma proteins are separated from serum by clotting prior to centrifugation.

20 Haemoglobin (Hb), bilirubin (Bili) and light-scattering substances like lipid particles are typical substances which will interfere with, and affect spectrophotometric and other blood analytical measurements. Such substances are referred to as interferents.

25 Many tests conducted on plasma or serum samples employ a series of reactions which terminate after the generation of chromophores which facilitate detection by spectrophotometric measurements at one or two wavelengths. Measurement of interfering substances prior to conducting such tests is important in providing meaningful and accurate test results. In fact if a sample is sufficiently

contaminated with interferents, tests are normally not conducted as the results will not be reliable.

5 In analytical laboratories bar codes are increasingly being used to identify samples, and such laboratories routinely analyze a variety of biologic fluids, for example, the most common being blood and urine.

10 Specimen integrity directly affects the accuracy of test results. Numerous factors can compromise specimen integrity such as, having the right sample eg., blood rather than urine; in the case of a blood sample, whether it is serum or plasma; the presence of interferents in a plasma or serum sample; the volume of the sample; the sample temperature; and the location of the upper surface of a gel barrier, which is also referred to herein as the gel level, in a blood sample, where the gel is an inert material used to separate serum or plasma from clotted or
15 packed blood cells, respectively. Finally, it is critical that the sample tested be properly matched to the results of any assessments on the sample.

20 Current methods used for quality assurance and specimen integrity rely principally on visual inspection of the specimen with or without comparison to a reference chart, depending upon which variable is being assessed. Visual inspection of samples is sometimes employed on a retrospective basis where there is disagreement between test results and clinical status of the patient in order to help explain such discrepancies.

25 A sample of plasma or serum is normally transferred from the original tube to a secondary tube. These secondary tubes may be amber coloured to protect photo sensitive constituents. Amber colouring makes visual inspection virtually impossible. On occasion, labels cover portions of the tube further restricting a full

- 3 -

visual examination. Further, it is sometimes difficult to distinguish between urine and plasma or serum samples, even in transparent tubes.

5 Pre-test screening of specimens by visual inspection is semi-quantitative at best, and highly subjective and may not provide the quality assurance required.

10 Furthermore, visual inspection of specimens is a time consuming, rate limiting process. Consequently, state-of-the-art blood analyzers in fully and semi-automated laboratories do not employ visual inspection of specimens. However, other methods such as direct sampling are not rapid enough or cost effective. In order to obtain a measurement of the sample of the plasma or serum, specimen tubes must be uncapped, a direct sample of the specimen taken and diluted prior to measurement.

15 DISCLOSURE OF INVENTION

The disadvantages of the prior art may be overcome by providing a rapid and accurate method and apparatus for monitoring blood specimens before samples are presented for analysis.

20 In one aspect of the invention, the bar code on the specimen tube is read to identify the specimen, as well, the bar code reading, determination of the gel level of the specimen and the height of fluid above the gel provide the basis for positioning the specimen container so that spectral data can be obtained. The spectral data is used in a novel way to determine if the specimen which is
25 presented for analysis contains interferents and if so, to what extent; to determine specimen type, for example if it is urine or plasma or serum; and to determine the temperature of the specimen.

- 4 -

In another aspect of the invention, there is provided an apparatus which incorporates: A. a device to read any bar code present on a specimen container and thereby identify and provide information with respect to positioning the specimen; B. a device to determine the location of the upper surface of a gel barrier of the specimen and the height of fluid above the gel; and C. A spectrophotometric device to irradiate and measure radiation from the specimen so as to determine if the specimen which is presented for analysis contains interferences and if so, to what extent; to determine specimen type; and to determine the temperature of the specimen. This apparatus is capable of these determinations where the sample tube containing the specimen has a sample identification label on the exterior surface.

In a further aspect of the invention, there is provided a method for the following: to read any bar code present on specimen container and thereby identify and provide information with respect to positioning the specimen; to determine the location of the upper surface of a gel barrier of the specimen and the height of fluid above the gel; to determine if the specimen which is presented for analysis contains interferences and if so, to what extent; to determine specimen type; and to determine the temperature of the specimen. The method of this invention allows for these determinations where the sample tube containing the specimen has a sample identification label on the exterior surface.

In yet another aspect of the invention, there is provided an apparatus and a method for the determinations described herein where the radiation from the spectrophotometer, or other appropriate source, is transmitted through the label, container and specimen.

In one embodiment, the bar code reading as well as the gel level and height of fluid above the gel are first determined. This determination provides information

- 5 -

essential for proper positioning of the sample for the following determinations. The concentration of interferents such as hemoglobin (Hb), total bilirubin (calibrated for unconjugated bilirubin, conjugated bilirubin, and delta bilirubin, the sum of results for these three gives total bilirubin) and lipids are determined by measurement of absorption of different wavelengths of light in serum or plasma specimens which are then compared with values obtained through calibration using reference measurements for the respective interferents in serum or plasma specimens. This is true also for determination of temperature of the sample. A determination of specimen type, for example whether the specimen is urine or plasma or serum, is also made. This determination is made by recordal of spectral data for different samples then through statistical analysis, the spectra are classified according to sample type. In addition a bar code reading is carried out either simultaneously, before or after the determination of the other parameters. To those skilled in the art, it is clear that although certain sequences of determinations are outlined here, any combination or sequence of combinations is within the scope of this invention.

In another embodiment, the bar code reading as well as the gel level and height of fluid above the gel are first determined. This determination provides information essential for proper positioning of the sample for the following determinations. The concentration of interferents such as hemoglobin (Hb), total bilirubin (calibrated for unconjugated bilirubin, conjugated bilirubin, and delta bilirubin, the sum of results for these three gives total bilirubin) and lipids are determined by measurement of reflectance of different wavelengths of light in serum or plasma specimens which are then compared with values obtained through calibration using reference measurements for the respective interferents in serum or plasma specimens. This is true also for determination of temperature of the sample. A determination of specimen type, for example whether the specimen is urine or plasma or serum, is also made. This

- 6 -

determination is made by recordal of spectral data for different samples then through statistical analysis, the spectra are classified according to sample type. In addition a bar code reading is carried out either simultaneously, before or after the determination of the other parameters. To those skilled in the art, it is clear that although certain sequences of determinations are outlined here, any combination or sequence of combinations is within the scope of this invention.

BRIEF DESCRIPTION OF DRAWINGS

Figure 1 is a longitudinal cross-section of a sample holder adapted for use with LED and radiation source.

Figure 2 is a top view of the complete sample holder of Figure 1.

Figure 3 is a longitudinal cross-section of a sample holder adapted for use with a laser and radiation source.

Figure 4 is a top view of the complete sample holder of Figure 3.

DESCRIPTION OF PREFERRED EMBODIMENTS

In operation, the apparatus first conducts a determination of the bar code and its position on the tube, and, based on the latter determination the tube is presented to the specimen holder 2 in a position so that the bar code does not interfere with the measurement process.

With respect to measuring gel level and height of fluid 26 above the gel 24, the specimen is placed in a specimen holder 2 of Figure 1, which will also contain a linear array of LEDs 16 on one side of the tube, and a corresponding array of silicon detectors 20 on the opposite side of the tube. The LEDs 16 are coupled

- 7 -

by electrical connections 6 to an electronic driver 4. The detectors 20 are coupled by electrical connections 7 to a microprocessor (not shown) which analyzes output. The number of LEDs and detectors will depend on the length of the tube, e.g., for a commonly used tube of length 10 cm, 22 LEDs and 20 detectors arranged 5 mm apart will be necessary to accommodate from a completely filled tube to an empty tube. In operation the first detector at the top of the column monitors as the three LED's opposite are flashed in succession: one which is directly opposite, one 5 mm above, and one 5 mm below. The measured distance between the LEDs and the detectors is used to determine tube diameter. This measurement is performed electronically, mechanically or optically, or in any combination of these. In a preferred embodiment this measurement is performed by a combination of mechanical and electronic operations. The fluid volume is calculated from the measured tube diameter and the measured height of fluid above the gel barrier.

Alternatively, with respect to measuring gel level and height of fluid, a diode laser 28 provides the radiation source wherein the source is focussed through a series of lenses 30 to spread the radiation 32 across the length of the sample tube. The light being transmitted through the sample tube is passed through a further series of lenses 34 and directed onto a PDA sensor 36. Again, through this apparatus the tube is analyzed in 1mm increments and the results are correlated to liquid height 26 and gel level 24. It is readily apparent that either approach also allows for the determination of the hematocrit of any blood sample. This is achieved by centrifuging a whole blood sample in a container into two phases, one being the blood cells and the other being serum or plasma. The container is then scanned by the present invention and the length of the container that each of the phases occupies is thereby determined. With this data the ratio of the length amounts of the cellular phase and of the serum or plasma phase is converted to hematocrit value.

- 8 -

Based upon the results from the above determinations, the relative positions of the tube and the fibre optics can be adjusted so as to optimize the position of the fluid compartment for subsequent determinations. Consequently, there is space 11 between the walls of the sample holder 2 and the fibre optics 10 and 14 to allow for such adjustments.

With respect to determination of sample type, temperature, as well as for measurement of interferents, reference is made to Figure 2. The sample 22 is placed into a specimen holder 2 (see Figure 1 for longitudinal view) which is located in a housing (not shown). A radiation source 8, capable of emitting radiation in a range from about 400nm to 2,500nm, is optically connected by fibre optics 10 to the sample. In operation where absorbance is measured the light source is directed through the sample, and the transmitted radiation is detected by a sensor 12, which is a photo diode array (PDA), that is located opposite the source. In operation where reflectance is measured, the detectors are proximate to the emission source (not shown). In both cases the detector is optically connected by fibre optics 14, or any other suitable means. In this apparatus the radiation source is split so that there is a reference beam which by-passes the sample. The apparatus also contains a means for correlating a sensor response, from the sample path relative to a sensor response from the reference path, to a quantity of a known substance in said sample. The housing has a cavity for receiving a sample and a lid for selectively opening and closing the cavity. The radiation source is for emitting a beam of radiation, and the sensor is responsive to receipt of radiation.

While the invention has been particularly shown and described with reference to certain embodiments, it will be understood by those skilled in the art that various other changes in form and detail may be made without departing from the spirit and scope of the invention.

WE CLAIM:

1. An apparatus for monitoring a specimen before said specimen is presented for clinical analysis, said apparatus comprised of:

- 5 a) means for holding a specimen container wherein said means and said container have a longitudinal axis;
- b) a first radiation source disposed to direct radiation at said specimen and a first radiation detector disposed to allow collection of transmitted or reflected radiation from said specimen;
- 10 c) electrical means to couple said first radiation source to an electronic driver;
- d) electrical means to couple said first radiation detector to a computing means which analyzes output from said detector for determination of at least one parameter about said specimen;
- 15 e) means to position said container in said axis of said holder based on results from said analysis;
- f) a second radiation source;
- g) means to transmit radiation from said second radiation source to said specimen;
- 20 h) means to spectrophotometrically detect transmitted or reflected radiation from said specimen; and
- i) means for correlating said detected radiation to determine the concentration of at least one interferent in said specimen.

25 2. The apparatus of claim 1 wherein said specimen is one of the group consisting of blood, serum, plasma or urine.

3. The apparatus of claim 1 wherein said first radiation source is comprised of a linear array of LEDs disposed along one side of said axis of said container

- 10 -

and said first radiation detector is comprised of a corresponding array of silicon detectors on the opposite side of the container to collect transmitted radiation and wherein a spectrophotometer provides the second radiation source and detectors.

5 4. The apparatus of claim 1 further comprising one or more lenses to focus said radiation from said first radiation source to spread said radiation across said axis of said container, and further wherein said apparatus contains one or more further lenses which collect transmitted or reflected radiation from said specimen and direct it to said spectrophotometric radiation detector.

10

5. The apparatus of claim 3 or 4 wherein said specimen container contains a sample identification label on the exterior surface of said container.

15

6. The apparatus of claim 3 or 4 wherein said first radiation and radiation from said spectrophotometer is transmitted through a label, a container and a specimen.

7. A method for monitoring specimens before said specimens are presented for clinical analysis comprising the steps of:

20

- a) placing a specimen in a specimen container;
- b) placing said specimen container into a holding means;
- c) applying radiation from a first radiation source to said specimen and collecting transmitted or reflected radiation from said specimen;
- d) analyzing said collected radiation to determine at least one parameter about said specimen; and
- e) based on results from said one or more determinations, positioning said container in said holder for further analysis wherein said further analysis comprises the steps of:

25

- 11 -

- i). spectrophotometrically applying radiation from a second radiation source to said specimen and detecting transmitted or reflected radiation from said specimen; and
- ii) correlating said spectrophotometrically detected radiation to determine the concentration of at least one interferent in said specimen.

5

8. The method of claim 7 wherein said container has a longitudinal axis and said radiation from said first radiation source is focussed through one or more lenses to spread said radiation across said axis of said container, said radiation being transmitted through said container and wherein reflected or transmitted radiation from said container is passed through one or more lenses and thereby directed to said radiation detector.

10

15

9. The method of claim 7 wherein said container has a longitudinal axis and said radiation from said first radiation source is applied through a linear array of LEDs disposed along on one side of said axis of said container and said transmitted or reflected radiation is collected by a corresponding array of silicon detectors on the opposite side of said container.

20

10. The method of claim 8 or 9 wherein said specimen is one of the group consisting of blood, serum, plasma or urine.

25

11. The method of claim 8 or 9 where said specimen container contains a sample identification label on the exterior surface of said container and said radiation from said first and second radiation sources is transmitted through said label, container and specimen.

- 12 -

12. The method of claim 8 or 9 wherein a bar code is present on said container and said bar code is read to identify said specimen.

5 13. The method of claim 7, 8 or 9 wherein the parameter determined is one or more of the group consisting of a gel level, the thickness of said gel, the height of fluid above said gel, and the volume of fluid above said gel.

10 14. The method of claim 7, 8 or 9 wherein said spectrophotometrically detected radiation is used to determine the concentration of one or more of the group consisting of hemoglobin, total bilirubin, unconjugated bilirubin, conjugated bilirubin, delta bilirubin, biliverdin, and lipid.

15 15. The method of claim 14 wherein said spectrophotometrically detected radiation is used to determine the temperature of said specimen.

16. The method of claim 14 wherein said spectrophotometrically detected radiation is used to determine the type of said specimen.

20 17. A method for monitoring blood specimens in specimen containers before said specimens are presented for clinical analysis comprising the steps of:

- a) reading any bar code on said container;
- b) determining the location of a gel level of said specimen and the height of any fluid located above said gel
- 25 c) on the basis of said determination positioning said container such that spectral data can be obtained; and
- d) interpreting said spectral data to determine the concentration of one or more intereferents and specimen type and specimen temperature.

- 13 -

18. The method of claim 17 wherein said determinations are made when said container has a label on the exterior surface of said container and said determinations are made through said label.

5

19. The method of claim 17 wherein said interferents are selected from the group consisting of hemoglobin, total bilirubin, unconjugated bilirubin, conjugated bilirubin, delta bilirubin, biliverdin, and lipid.

10

20. A method of determining the hematocrit of a blood sample comprising the steps of:

- a) centrifuging a whole blood sample in a tube having an axis, to separate the sample into two phases, one being the blood cells and the other the serum or plasma;
- b) while maintaining said phases separate, optically scanning the phases in said tube along said tube axis to determine a length of said axis that each of said phases occupies;
- c) calculating the ratio of the axis length amounts of the cellular phase and of the serum or plasma phase; and
- d) converting said ratio to hematocrit value.

15

20

1/2




FIG. 1




FIG. 2

2/2




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

ional Application No
PCT/CA 96/00758

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 G01N21/27

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 9, no. 239 (P-391), 25 September 1985 & JP 60 093348 A (MOCHIDA SEIYAKU), 25 May 1985, see abstract	20
A	---	2,3,9,10
A	US 4 338 279 A (OLYMPUS OPTICAL) 6 July 1982 see column 1, paragraph 1 see column 2, line 51 - column 3, line 5 see column 5, line 52 - line 58 see column 6, line 3 - line 29; figure 1 ---	1,2,7, 10,17
A	US 4 252 438 A (HAINA) 24 February 1981 see abstract see column 5, line 43 - line 57; figure 1 ---	1,2,7, 10,17
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

19 March 1997

Date of mailing of the international search report

26.03.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Thomas, R.M.

INTERNATIONAL SEARCH REPORT

ional Application No
PCT/CA 96/00758

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 28 25 659 A (PIFFL) 20 December 1979 see page 4, line 3 - line 7 see page 4, line 17 - line 28; figures 1,2 ---	2-4,8-10
A	PATENT ABSTRACTS OF JAPAN vol. 8, no. 278 (P-322) [1715] , 19 December 1984 & JP 59 145964 A (DENKI KAGAKU KEIKI), 21 August 1984, see abstract ---	2,4,8,10
A	EP 0 479 622 A (TOA) 8 April 1992 see column 1, paragraph 1 - paragraph 2 -----	2,5,10, 12,17

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/CA 96/00758

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4338279 A	06-07-82	JP 1473451 C JP 55136957 A JP 63021139 B DE 3014250 A	27-12-88 25-10-80 02-05-88 16-10-80
US 4252438 A	24-02-81	DE 2727400 A CH 629597 A FR 2394797 A GB 2002108 A,B JP 54008589 A NL 7806392 A SE 7806964 A	21-12-78 30-04-82 12-01-79 14-02-79 22-01-79 20-12-78 19-12-78
DE 2825659 A	20-12-79	NONE	
EP 0479622 A	08-04-92	AU 625029 A CA 2050165 A DE 69112752 D DE 69112752 T US 5286959 A	25-06-92 06-04-92 12-10-95 15-02-96 15-02-94